

Title (en)  
SEALING DEVICE FOR ROLL BEARING

Publication  
**EP 0297323 A3 19890621 (DE)**

Application  
**EP 88109192 A 19880609**

Priority  
DE 3721264 A 19870627

Abstract (en)  
[origin: EP0297323A2] The device has reinforcing elements 12 to 15. During the operation of such a sealing device, it has been found that zone 26 of the sealing device tends to bend at high speeds of revolution. At the same time, the annular rib 18 and the annular lip 20 are pressed against the sealing surface 21. This results in high wear and premature failure. It is proposed to vulcanise a reinforcing element 24, 25 into zone 26 of the seal body. <IMAGE>

IPC 1-7  
**B21B 31/07**

IPC 8 full level  
**B21B 31/07** (2006.01)

CPC (source: EP KR)  
**B21B 31/07** (2013.01 - KR); **B21B 31/078** (2013.01 - EP)

Citation (search report)  
• [AD] DE 3601238 A1 19860828 - MORGAN CONSTRUCTION CO [US]  
• [X] US 3330567 A 19670711 - MERCER CHARLES S, et al  
• [A] FR 1339944 A 19631011 - MORGAN CONSTRUCTION CO  
• [A] GB 2076481 A 19811202 - MORFAN CONSTRUCTION CO

Cited by  
EP1609542A1; CN102893040A; US2012134831A1; US8366390B2; CN100391634C; CN114122989A; US8215647B2; WO2008092616A1; WO2005037455A1

Designated contracting state (EPC)  
AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)  
**EP 0297323 A2 19890104; EP 0297323 A3 19890621**; AU 1635288 A 19890105; DD 271066 A5 19890823; DE 3721264 A1 19890112; JP S6422408 A 19890125; KR 900000134 A 19900130; PL 273005 A1 19890306; YU 119388 A 19901231; ZA 883849 B 19881215

DOCDB simple family (application)  
**EP 88109192 A 19880609**; AU 1635288 A 19880517; DD 31695288 A 19880620; DE 3721264 A 19870627; JP 15510088 A 19880624; KR 880007024 A 19880611; PL 27300588 A 19880610; YU 119388 A 19880622; ZA 883849 A 19880530