

Title (en)
PLANT FOR SEPARATELY CASTING METALLURGICAL SLAG AND METAL MELT FROM A METAL-MELT/METALLURGICAL-SLAG MIXTURE

Publication
EP 0298074 B1 19910925 (DE)

Application
EP 88890163 A 19880623

Priority
AT 168187 A 19870703

Abstract (en)
[origin: EP0298074A2] The plant has a casting vessel (2) provided with a pouring spout (6) which is to take the molten metal/metallurgical slag mixture and which is pivotable about an approximately horizontal pivoting axis (29), and a slag casting mould (5). For reliable prevention of molten metal running off with the molten slag when the latter is poured out onto the slag casting mould (5), with the lowest possible expenditure on equipment, provision is made between the pouring spout (6) of the casting vessel (2) and the slag casting mould (5) for a pivotable casting channel (7) which can be pivoted from a slag-casting position (A), in which the metallurgical slag is taken from the pouring spout (6) via the casting channel (7) to the slag-casting mould (5), into a metal-casting position (B), in which molten metal is taken from the pouring spout (6) to a molten metal receiver vessel (17). <IMAGE>

IPC 1-7
C21B 3/06; C21C 5/36; F27D 3/14

IPC 8 full level
C21B 7/14 (2006.01); **F27D 3/15** (2006.01)

CPC (source: EP)
C21B 7/14 (2013.01); **F27D 3/1545** (2013.01)

Citation (examination)
PATENT ABSTRACT OF JAPAN, Band 4, Nr. 106 (C-20)(588), 30. Juli 1980; & JP - A -55 69207 (NIPPON KOKAN) 24.05.1980

Cited by
US5409969A; AT503049B1

Designated contracting state (EPC)
BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
EP 0298074 A2 19890104; EP 0298074 A3 19890222; EP 0298074 B1 19910925; AT 387738 B 19890310; AT A168187 A 19880815; CN 1008516 B 19900627; CN 1031667 A 19890315; DE 3865120 D1 19911031

DOCDB simple family (application)
EP 88890163 A 19880623; AT 168187 A 19870703; CN 88104050 A 19880702; DE 3865120 T 19880623