

Title (en)  
SCROLL-TYPE DISPLACEMENT ENGINE

Publication  
**EP 0298315 B1 19910123 (DE)**

Application  
**EP 88110070 A 19880624**

Priority  
CH 263887 A 19870710

Abstract (en)  
[origin: JPS6424192A] PURPOSE: To surely seal a work chamber for long hours by forming a spring member arranged between a sealing strip and a groove bottom from a tube made of silicon rubber, relating to a displacement machine for compressible media. CONSTITUTION: On both sides of a disk 4 a displacement body 5 extending spirally is disposed. The displacement body 5 is engaged with the exhaust chamber 6 of a casing 7. On the end face of the displacement body 5 an annular groove 13 is provided and into the groove 13, an elastic sealing strip 14 made of a material possible to slide, is inserted. A spring member 15 is disposed between the sealing strip 14 and the groove bottom. The spring member 15 consists of a tube made of a silicone rubber. Thus, the work chamber can be surely and satisfactorily sealed over long hours of operation.

IPC 1-7  
**F01C 19/08**

IPC 8 full level  
**F04C 18/02** (2006.01); **F01C 19/08** (2006.01)

CPC (source: EP US)  
**F01C 19/08** (2013.01 - EP US)

Citation (examination)  
Technik-Lexikon Werkstoffe und Werkstoffprüfung Grundlagen, Band 4, Rowohlt Taschenbuch Verlag GmbH, 1971, Seite 673

Cited by  
US5258046A; EP0597804A1; EP0807759A3; EP0446635A3; EP0520487A1; CN101960142A; US8721304B2

Designated contracting state (EPC)  
AT BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)  
**EP 0298315 A1 19890111; EP 0298315 B1 19910123**; AT E60405 T1 19910215; BR 8803459 A 19890131; CH 673135 A5 19900215; DE 3861635 D1 19910228; JP S6424192 A 19890126; US 4883413 A 19891128

DOCDB simple family (application)  
**EP 88110070 A 19880624**; AT 88110070 T 19880624; BR 8803459 A 19880708; CH 263887 A 19870710; DE 3861635 T 19880624; JP 16786888 A 19880707; US 21434088 A 19880701