

Title (en)
DEVICE FOR ATTACHING A PRINTING AND/OR SPREADING DOCTOR

Publication
EP 0298911 A3 19900704 (DE)

Application
EP 88810342 A 19880526

Priority
CH 255987 A 19870706

Abstract (en)
[origin: EP0298911A2] To secure the printing doctor (10) above the printing screen, the doctor inside the cavity (2) of the hollow profile (1) is pressed against a wall (13) of the cavity (2) by means of a clamping tube (3) lying in a longitudinal groove (4) and being supplied with by a pressure medium. The tube (3) is made of elastic material; it therefore enables the printing doctor (10) to be secured with a uniform linear contact pressure over its whole length. Consequently, there is no danger that the printing doctor (10) can distort as a result of local areas of unevenness on its surface which could give rise to local differences in contact pressure. <IMAGE>

IPC 1-7
B41F 15/42; **B41F 15/44**

IPC 8 full level
B41F 15/40 (2006.01); **B41F 15/42** (2006.01)

CPC (source: EP KR US)
B41F 15/40 (2013.01 - KR); **B41F 15/42** (2013.01 - EP US); **Y10T 403/22** (2015.01 - EP US); **Y10T 403/7062** (2015.01 - EP US)

Citation (search report)
• [Y] DE 1916725 A1 19691030 - LODDING ENGINEERING CORP
• [Y] FR 2302199 A1 19760924 - ALSACIENNE CONSTR MECA [FR], et al
• [Y] US 4102266 A 19780725 - PORTH FRANK L
• [Y] FR 2383789 A1 19781013 - BLACK JAMES [US]
• [Y] US 4549933 A 19851029 - JUDD MICHAEL [US], et al
• [Y] GB 800607 A 19580827 - HAROLD ERIC BALIOL SCOTT
• [A] DE 3523450 A1 19860109 - WAERTSILAE OY AB [FI]

Cited by
CN103448357A; EP0391843A1; CH677641A5; WO9631350A1

Designated contracting state (EPC)
AT BE DE ES FR GB GR IT NL SE

DOCDB simple family (publication)
EP 0298911 A2 19890111; **EP 0298911 A3 19900704**; CH 676694 A5 19910228; CN 1030548 A 19890125; JP S6424750 A 19890126; KR 890001737 A 19890328; US 4940354 A 19900710

DOCDB simple family (application)
EP 88810342 A 19880526; CH 255987 A 19870706; CN 88104149 A 19880705; JP 16763488 A 19880705; KR 880007414 A 19880620; US 20716588 A 19880615