

Title (en)

METHOD AND DEVICE FOR SUPPLYING A SEPARATOR WITH PRINTED PRODUCTS

Publication

EP 0300179 B1 19910327 (DE)

Application

EP 88108955 A 19880604

Priority

CH 282187 A 19870724

Abstract (en)

[origin: EP0300179A1] Printed products (14) are released from the incoming flow (T) of overlapping products by means of a separating arrangement (58) and supplied to the buffer branch (30). The printed products (14) which are not released are passed by the supply means (22) to the feeder (12) while forming an overlapping-product buffer. In the buffer branch (30), the released printed products (14) are wound in overlapping formation (U) onto a buffer reel (64) by means of a buffer-reel band (68). In the event of gaps in the incoming flow (T), the printed products (14) stored in the buffer reel (64) are unwound and fed to the supply means (22), so that the overlapping formation (S) is not interrupted. Since the buffer reel (64) has a considerable storage capacity, it is possible even for relatively long gaps in the flow (T) supplied to be bridged without needing to adjust the functioning of the feeder (12). <IMAGE>

IPC 1-7

B65H 5/28; **B65H 5/34**; **B65H 29/60**

IPC 8 full level

B65H 29/51 (2006.01); **B65H 5/28** (2006.01); **B65H 29/66** (2006.01)

CPC (source: EP US)

B65H 5/28 (2013.01 - EP US); **B65H 2701/1932** (2013.01 - EP US); **Y10S 271/902** (2013.01 - EP US)

Citation (examination)

DE 3244663 A1 19830721 - FERAG AG [CH]

Cited by

US5579889A; EP0876977A1; US6193227B1; WO9402398A1

Designated contracting state (EPC)

CH DE FR IT LI SE

DOCDB simple family (publication)

EP 0300179 A1 19890125; **EP 0300179 B1 19910327**; DE 3862176 D1 19910502; JP S6438371 A 19890208; US 4953843 A 19900904

DOCDB simple family (application)

EP 88108955 A 19880604; DE 3862176 T 19880604; JP 17251888 A 19880711; US 22395888 A 19880721