

Title (en)  
ELECTROPHOTOGRAPHIC PHOTSENSITIVE MEMBER

Publication  
**EP 0300807 A3 19900801 (EN)**

Application  
**EP 88306746 A 19880722**

Priority  
JP 18348087 A 19870724

Abstract (en)  
[origin: EP0300807A2] An electrophotographic photosensitive member, comprises an electroconductive support (1), optionally a charge blocking layer (2), a photoconductive layer (3,4) made from hydrogen-containing amorphous silicon as a matrix and a charge injection blocking layer (5). To give the member high electrostatic charge acceptance and a good photosensitivity, the charge injection blocking layer (5) has a different conductivity type from that of the photoconductive layer (3,4) and a broader optical band gap than that of the photoconductive layer (3,4). A moisture and corona-resistant layer (6) is also provided.

IPC 1-7  
**G03G 5/082**

IPC 8 full level  
**G03G 5/08** (2006.01); **G03G 5/082** (2006.01)

CPC (source: EP)  
**G03G 5/08235** (2013.01); **G03G 5/0825** (2013.01)

Citation (search report)  
• [A] EP 0176936 A1 19860409 - TOSHIBA KK [JP]  
• [A] FR 2490359 A1 19820319 - CANON KK [JP]  
• [A] PATENT ABSTRACTS OF JAPAN vol. 11, no. 58 (P-550)(2505) 21 February 1987, & JP-A-61 223 752 (KOBE STEEL LTD) 04 October 1986,

Cited by  
US8969711B1; US5737671A; EP0809153A3; EP0764887A3; US5738963A; US9947824B1

Designated contracting state (EPC)  
CH DE FR GB LI NL SE

DOCDB simple family (publication)  
**EP 0300807 A2 19890125; EP 0300807 A3 19900801; JP S6428654 A 19890131**

DOCDB simple family (application)  
**EP 88306746 A 19880722; JP 18348087 A 19870724**