

Title (en)

SAFETY DEVICE FOR PNEUMATIC SUSPENSIONS

Publication

EP 0301304 B1 19910703 (EN)

Application

EP 88111093 A 19880712

Priority

IT 2150987 A 19870730

Abstract (en)

[origin: EP0301304A1] A safety device (1) for pneumatic suspensions (2) comprises a flange (14) fixed under a sprung mass (4) and having an opening (15) around which is tightened the edge (8b) of a membrane (8) interposed between the sprung mass (4) and an unsprung mass (3), forming thus an enclosure (9) filled with a fluid under pressure. A movable cap (19) is slidably guided vertically in the opening (15). A sealing element (22) is provided between the cap (19) and the flange (14). During normal working conditions the cap (19) is pushed towards the sprung mass (4) by the fluid pressure, against a spring (28) placed between the cap (19) and a plate (18) fixed to the sprung mass (4). Should the membrane burst, the cap (19) would be pushed by spring (28) against a checking element (11a) connected to the unsprung mass (3).

IPC 1-7

B61F 5/12; **B61F 5/14**; **B61F 5/16**

IPC 8 full level

A62C 3/00 (2006.01); **B61F 5/10** (2006.01); **B61F 5/12** (2006.01); **B61F 5/14** (2006.01); **B61F 5/16** (2006.01); **B61F 5/20** (2006.01)

CPC (source: EP)

A62C 3/00 (2013.01); **B61F 5/10** (2013.01); **B61F 5/127** (2013.01); **B61F 5/144** (2013.01); **B61F 5/148** (2013.01); **B61F 5/16** (2013.01); **B61F 5/20** (2013.01)

Cited by

CN103129575A; EP0488103A1; GB2463690A; US5950544A; EP3450280A1; JP2008302845A

Designated contracting state (EPC)

CH DE FR LI

DOCDB simple family (publication)

EP 0301304 A1 19890201; **EP 0301304 B1 19910703**; DE 3863504 D1 19910808; IT 1222392 B 19900905; IT 8721509 A0 19870730

DOCDB simple family (application)

EP 88111093 A 19880712; DE 3863504 T 19880712; IT 2150987 A 19870730