

Title (en)

IMPROVED ELECTROINJECTOR FOR FEEDING FUEL TO INTERNAL COMBUSTION ENGINES

Publication

**EP 0301620 A3 19900207 (EN)**

Application

**EP 88201411 A 19880706**

Priority

IT 2145087 A 19870727

Abstract (en)

[origin: EP0301620A2] The electroinjector is equipped with a central magnetic core (10) from which a guide tube (19) protrudes, which acts as a guide for an anchor (12) of ferromagnetic material, which bears the injector shutter (17). In a form of practical embodiment, the anchor (12), in its opening movement, comes to stop against a shoulder element (24) made from an amagnetic material fastened on the core (10) in such a protruding position, as to define an air gap (T) and prevent the core (10) and the anchor (12) from magnetically sticking to each other. The shoulder element (24) is provided with a fastening cylindrical portion (30), and an adjacent portion (31) with a prevailingly radial development, which acts as the stop portion. The element, which can also be fastened onto the anchor (10), can be obtained from a rolled sheet or by drawing a thin tube.

IPC 1-7

**F02M 51/06**

IPC 8 full level

**F02M 51/06** (2006.01); **H01F 7/08** (2006.01)

CPC (source: EP)

**F02M 51/0667** (2013.01); **H01F 7/088** (2013.01)

Citation (search report)

- [XP] WO 8804727 A1 19880630 - LUCAS IND PLC [GB]
- [Y] EP 0172591 A1 19860226 - SPICA SPA [IT]
- [A] GB 2058466 A 19810408 - BOSCH GMBH ROBERT
- [AP] GB 2198589 A 19880615 - HITACHI LTD, et al

Cited by

EP1279826A1; EP0398157A3; EP1088986A1; WO9516125A1; WO9303272A1; WO9716641A1; WO9407021A1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**EP 0301620 A2 19890201; EP 0301620 A3 19900207; IT 1222137 B 19900905; IT 8721450 A0 19870727**

DOCDB simple family (application)

**EP 88201411 A 19880706; IT 2145087 A 19870727**