

Title (en)

Method and apparatus for terminating an optical fiber.

Title (de)

Verfahren und Gerät zum Abschliessen einer optischen Faser.

Title (fr)

Méthode et appareil pour terminer une fibre optique.

Publication

EP 0301775 A2 19890201 (EN)

Application

EP 88306772 A 19880722

Priority

US 8013787 A 19870731

Abstract (en)

A method and apparatus for supporting an optical fiber (10) in a ferrule assembly (20) is disclosed. The ferrule assembly (20) includes an elongate ferrule body (22) having a fiber insertion end (23), a fiber egressing end (24) and an elongate bore (25) therebetween. A fiber capillary (30) is supported in the bore (25) of the body (22) having a precision aperture (35) therethrough which accommodates the optical fiber (10). The capillary (30) includes a first end extend (32) which extends beyond the egressing end (24) of the ferrule body (22) so that the optical fiber (10) and the capillary (30) may be polished to form a uniform flat end surface extending beyond the ferrule end.

IPC 1-7

G02B 6/38

IPC 8 full level

G02B 6/36 (2006.01); **B24B 19/22** (2006.01); **G02B 6/38** (2006.01)

CPC (source: EP US)

B24B 19/226 (2013.01 - EP US); **G02B 6/3835** (2013.01 - EP US); **G02B 6/3874** (2013.01 - EP US); **G02B 6/3854** (2013.01 - EP US)

Cited by

EP0506004A1; EP0455290A1; DE19906434A1; EP0457269A3; WO2004017115A1

Designated contracting state (EPC)

BE CH DE ES FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0301775 A2 19890201; **EP 0301775 A3 19891004**; **EP 0301775 B1 19940921**; AU 1975288 A 19890202; AU 601865 B2 19900920; CA 1315137 C 19930330; DE 3851594 D1 19941027; DE 3851594 T2 19950316; JP S6470712 A 19890316; US 4815809 A 19890328

DOCDB simple family (application)

EP 88306772 A 19880722; AU 1975288 A 19880722; CA 572884 A 19880722; DE 3851594 T 19880722; JP 18849988 A 19880729; US 8013787 A 19870731