

Title (en)

METHOD FOR PRODUCING OXIDIZED FILAMENTS

Publication

EP 0301915 B1 19930224 (EN)

Application

EP 88307084 A 19880801

Priority

JP 19030187 A 19870731

Abstract (en)

[origin: EP0301915A2] In a method for producing oxidized filaments (102) by treating precursor filaments (101) in a bed (5a) fluidized by an oxidizing gas and heat treating the precursor filaments (101) in the fluidized bed (5a), the fluidized bed (5a) is formed with heat-medium particles (5), not less than 80% by weight of which are of solid particles each having a particle diameter of not greater than 10 mesh, and the oxidation is carried out under optimum conditions within an optimum range of the treatment temperatures, an optimum range of depths H of the fluidized bed (5a) and an optimum gas speed of the oxidizing gas. By the method, the period of time required for the oxidation can be greatly shortened and oxidized filaments (102) having excellent characteristics can be obtained Furthermore, where the oxidized filaments thus obtained are carbonized, carbon fibers having excellent mechanical properties can be produced.

IPC 1-7

D01F 9/22

IPC 8 full level

D01F 9/22 (2006.01); **D06M 11/34** (2006.01)

CPC (source: EP KR)

D01F 9/12 (2013.01 - KR); **D01F 9/225** (2013.01 - EP); **D06M 11/34** (2013.01 - EP)

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0301915 A2 19890201; **EP 0301915 A3 19891129**; **EP 0301915 B1 19930224**; DE 3878606 D1 19930401; DE 3878606 T2 19930812; KR 890002459 A 19890410

DOCDB simple family (application)

EP 88307084 A 19880801; DE 3878606 T 19880801; KR 880009712 A 19880730