

Title (en)

Process for reducing agglomerate disaggregation.

Title (de)

Verfahren zur Verringerung des Kornzerfalls.

Title (fr)

Procédé pour diminuer la désagrégation d'agglomérés.

Publication

EP 0302000 A2 19890201 (DE)

Application

EP 88730124 A 19880525

Priority

- DE 3725874 A 19870730
- DE 3733480 A 19871001

Abstract (en)

The invention relates to a process for inexpensively providing a sinter suitable for use in a blast furnace by treatment of the sinter. To improve a conventional treatment process in such a way that corrosion is reduced and the sinter is treated in an environmentally more acceptable way, that, if possible, only a part quantity of the sinter production is treated, a sinter of enhanced disaggregation value can be used and nevertheless the blast furnace campaign is not impaired, it is proposed that sinter material produced on a sintering belt is divided in a manner known per se by precrushing and screening into material which is too fine-grain for use in the blast furnace ("returns"), material which can be used directly ("use grain size I") and too coarse material ("oversize"), that the oversize is converted by further crushing into a grain size which can be used ("use grain size II") and at least the use grain size II is treated with sulphur-containing reagents.

Abstract (de)

Die Erfindung betrifft ein Verfahren zur kostengünstigen Bereitstellung eines für den Einsatz in einem Hochofen geeigneten Sinters durch Behandeln des Sinters. Um ein herkömmliches Behandlungsverfahren so zu verbessern, daß Korrosion verhindert wird und eine umweltfreundlichere Behandlung des Sinters erfolgt, daß ggf. nur eine Teilmenge der Sinterproduktion behandelt wird, ein Sinter mit erhöhtem Zerfallswert eingesetzt werden kann und trotzdem keine Beeinträchtigung des Hochofenganges eintritt wird vorgeschlagen, daß ein auf einem Sinterband erzeugtes Sintergut in an sich bekannter Weise durch Vorbrechen und Seiben in für den Hochofeneinzatz zu feinkörniges Gut ("Rückgut"), unmittelbar einsatzfähiges Material ("Einsatzkörnung I") und eine zu grobes Gut ("Überkorn") unterteilt wird, daß das Überkorn durch Nachbrechen in einsatzfähige Körnung umgewandelt wird ("Einsatzkörnung II") und zumindest die Einsatzkörnung II mit schwefelhaltigen Reagenzien behandelt wird.

IPC 1-7

C21B 5/00; C22B 1/16

IPC 8 full level

C21B 5/00 (2006.01); **C22B 1/16** (2006.01); **C22B 1/20** (2006.01)

CPC (source: EP)

C21B 5/008 (2013.01); **C22B 1/16** (2013.01)

Cited by

US11549159B2

Designated contracting state (EPC)

BE ES FR GB IT

DOCDB simple family (publication)

EP 0302000 A2 19890201; EP 0302000 A3 19900321; EP 0302000 B1 19920819; DE 3733480 C1 19890119; ES 2034358 T3 19930401;
JP S6439329 A 19890209

DOCDB simple family (application)

EP 88730124 A 19880525; DE 3733480 A 19871001; ES 88730124 T 19880525; JP 18667288 A 19880726