

Title (en)
RIVET SETTING TOOL FOR SETTING BLIND RIVETS

Publication
EP 0302128 B1 19920102 (DE)

Application
EP 87111206 A 19870804

Priority
EP 87111206 A 19870804

Abstract (en)
[origin: EP0302128A1] In a rivet setting tool for setting blind rivets, with a conveying channel which extends rearwards through the head of the implement from the mouthpiece and is intended for carrying away the mandrels which have been torn off, with an axial feed device which can be actuated for the upsetting operation and comprises a cylinder-piston arrangement consisting of a pneumatic piston and a hydraulic piston, and with a compressed-air supply arrangement for actuating the feed device and discharging the mandrels which have been torn off, an actuating member (27) can be moved into two operating positions. In the first operating position, it opens a conveying-channel valve (34, 44) which introduces compressed air into the conveying channel for the purpose of sucking up the rivet and, in the second operating position, opens a pneumatic-piston valve (43) for actuating the feed device (9). <IMAGE>

IPC 1-7
B21J 15/06

IPC 8 full level
B21J 15/00 (2006.01); **B21J 15/02** (2006.01); **B21J 15/06** (2006.01); **B21J 15/16** (2006.01); **B21J 15/18** (2006.01); **B21J 15/32** (2006.01); **B21J 15/34** (2006.01)

CPC (source: EP US)
B21J 15/105 (2013.01 - EP US); **B21J 15/32** (2013.01 - US); **B21J 15/326** (2013.01 - EP US); **Y10T 29/53739** (2015.01 - EP US); **Y10T 29/5377** (2015.01 - EP US)

Cited by
FR2706338A1; DE19826157A1; CN101856715A; US5697136A; CZ306423B6; GB2424609B; KR101022088B1; WO9638243A1; US7866018B2; WO2006106286A1

Designated contracting state (EPC)
DE FR GB IT SE

DOCDB simple family (publication)
EP 0302128 A1 19890208; **EP 0302128 B1 19920102**; DE 3775768 D1 19920213; JP 2523163 B2 19960807; JP H01104439 A 19890421; US 4866972 A 19890919

DOCDB simple family (application)
EP 87111206 A 19870804; DE 3775768 T 19870804; JP 19355288 A 19880804; US 22750388 A 19880802