

Title (en)  
Position-measuring device with plural probe placings.

Title (de)  
Positionsmesseinrichtung mit mehreren Abtaststellen.

Title (fr)  
Dispositif de mesure de position avec plusieurs points de capteur.

Publication  
**EP 0302194 A2 19890208 (DE)**

Application  
**EP 88108744 A 19880601**

Priority  
DE 3726260 A 19870807

Abstract (en)  
In this measuring device according to Figure 1, an index disc (3) is scanned twice, resulting in two scanning points (A1 and A2). The scanning signals (U1, U3; U2, U4) are supplied to a test circuit (P). If it is detected in the test circuit (P) that the phase relation between the scanning signals (U1 and U3 and U2 and U4) exceeds a limit value, one of the scanning points (A1 and A2) is given higher weighting than the other one. For this purpose, the proportion of the signals (U1, U2) of one scanning point (A1) is raised and the proportion of the signals (U3, U4) of the other scanning point (A2) is reduced. <IMAGE>

Abstract (de)  
Bei dieser Meßeinrichtung gemäß Figur 1 wird eine Teilscheibe (3) doppelt abgetastet, so daß sich zwei Abtaststellen (A1 und A2) ergeben. Die Abtastsignale (U1, U3; U2, U4) werden einer Prüfschaltung (P) zugeführt. Wenn in der Prüfschaltung (P) festgestellt wird, daß die Phasenbeziehung zwischen den Abtastsignalen (U1 und U3 bzw. U2 und U4) einen Grenzwert überschreitet, so wird eine der Abtaststellen (A1 und A2) höher gewichtet als die andere. Dazu wird der Anteil der Signale (U1, U2) einer Abtaststelle (A1) angehoben und der Anteil der Signale (U3, U4) der anderen Abtaststelle (A2) verringert. <IMAGE>

IPC 1-7  
**G01D 5/244**

IPC 8 full level  
**G01B 21/00** (2006.01); **G01B 21/22** (2006.01); **G01D 5/244** (2006.01); **G01D 5/245** (2006.01)

CPC (source: EP US)  
**G01D 5/24404** (2013.01 - EP US); **G01D 5/24476** (2013.01 - EP US)

Cited by  
DE102010048186B4; EP2278277A3; EP0394942A3; CN100408968C; EP2439498A1; EP1923670A1; DE19601674A1; DE19601674B4; EP0395936A1; CN102555507A; CN100429471C; DE102010048186A1; US7797981B2; WO2005017448A1; WO2005017447A1; US8729458B2; US10168134B2; US6935036B2; US7073271B2; EP1474649B1; EP1474650B1

Designated contracting state (EPC)  
AT CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)  
**EP 0302194 A2 19890208; EP 0302194 A3 19930519; EP 0302194 B1 19941117**; AT E114186 T1 19941215; DE 3726260 A1 19890216; DE 3726260 C2 19890524; DE 3852121 D1 19941222; JP 2565989 B2 19961218; JP S6459111 A 19890306; US 4990767 A 19910205

DOCDB simple family (application)  
**EP 88108744 A 19880601**; AT 88108744 T 19880601; DE 3726260 A 19870807; DE 3852121 T 19880601; JP 19287388 A 19880803; US 22283388 A 19880722