

Title (en)

A TOOL CUTTER HEAD

Publication

EP 0303346 B1 19911106 (EN)

Application

EP 88305995 A 19880701

Priority

IL 8352587 A 19870813

Abstract (en)

[origin: EP0303346A1] A cutter head (9) releasably mounted on a tool holder (1) and to be fitted with an exchangeable cutting insert (11a) whilst the tool holder (1) is adapted to be secured to a lathe or the like; a substantially U-shaped bushing (23) being articulatedly mounted in a recess (14) formed in an end of the cutter head (9) so as to define a receiver socket adapted to receive an engaging head (5) of a drawbar (2) longitudinally displaceable within the tool holder (1); the arrangement being such that with the engaging head (5) of the drawbar (2) located in said receiver socket, a traction force exerted on the drawbar (2) results in transverse abutting surfaces of the bushing (23) being displaced into a clamping abutment with corresponding transverse abutment surfaces formed on the tool holder (1).

IPC 1-7

B23B 29/04

IPC 8 full level

B23B 29/00 (2006.01); **B23B 29/04** (2006.01)

CPC (source: EP)

B23B 29/046 (2013.01); **B23B 2240/36** (2013.01)

Cited by

US5167478A; ES2067364A2; US6813984B1; WO9902877A1; WO9310930A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0303346 A1 19890215; EP 0303346 B1 19911106; AT E69188 T1 19911115; DE 3866056 D1 19911212; IL 83525 A0 19880131; IL 83525 A 19900726; JP 2531753 B2 19960904; JP S6451208 A 19890227; ZA 884741 B 19890329

DOCDB simple family (application)

EP 88305995 A 19880701; AT 88305995 T 19880701; DE 3866056 T 19880701; IL 8352587 A 19870813; JP 19074388 A 19880801; ZA 884741 A 19880701