

Title (en)
RECESSED LIGHT FITTING

Publication
EP 0304878 B1 19920311 (DE)

Application
EP 88113724 A 19880823

Priority
DE 3728520 A 19870826

Abstract (en)
[origin: US4870549A] An improved built-in ceiling light. The dimensions of openings provided in false ceilings for the installation of built-in ceiling lights result in light housing dimensions which do not always provide the necessary storage space for the electrical components, in particular the ballast. It is known to obtain this necessary storage space by means of a projection from a side wall on the side of the housing base. However, this impedes the installation assembly. To avoid this difficulty the improved ceiling light has a projection which is a lid pivotally mounted to a housing base and to which the electrical components are attached. Then, during the insertion of the light housing, the lid, together with the electrical components, can be pivoted sufficiently far through a rectangular opening in a longitudinal side wall into the light housing.

IPC 1-7
F21V 21/04

IPC 8 full level
F21S 8/02 (2006.01); **F21V 21/04** (2006.01); **F21V 23/00** (2006.01); **F21V 23/02** (2006.01)

CPC (source: EP US)
F21S 8/02 (2013.01 - EP US); **F21V 21/04** (2013.01 - EP US); **F21V 23/00** (2013.01 - EP US); **F21V 23/02** (2013.01 - EP US); **F21V 23/026** (2013.01 - EP US); **F21Y 2103/00** (2013.01 - EP US)

Cited by
DE102013202909B4; EP1055876A3; EP0545045A1; DE102013202909A1; DE19648310A1; EP2157370A3

Designated contracting state (EPC)
AT CH DE GB IT LI SE

DOCDB simple family (publication)
EP 0304878 A1 19890301; **EP 0304878 B1 19920311**; AT E73532 T1 19920315; DE 3869017 D1 19920416; NO 883830 D0 19880826; NO 883830 L 19890227; US 4870549 A 19890926; ZA 886272 B 19890426

DOCDB simple family (application)
EP 88113724 A 19880823; AT 88113724 T 19880823; DE 3869017 T 19880823; NO 883830 A 19880826; US 22401988 A 19880725; ZA 886272 A 19880824