

Title (en)

DEVICE FOR IMPARTING A FALSE-TWIST BY FRICTION TO AT LEAST ONE ADVANCING YARN

Publication

EP 0305305 B1 19910515 (FR)

Application

EP 88420289 A 19880825

Priority

FR 8712175 A 19870828

Abstract (en)

[origin: EP0305305A1] Device making it possible to impart a false twist by friction to a fibrous material. <??>It comprises two endless belts (1, 2) inclined relative to one another and mounted on two pairs of rollers (3, 4, 5, 6). <??>According to the invention, the supporting rollers (3, 4, 5, 6) which support the two belts (1, 2) are mounted on the actual housing (8) of the spindle by means of two supporting arms (9, 10, 11, 12), one of the supporting arms (10, 12) of each pair being subjected to the action of pressure means making it possible to ensure the tension of each belt (1, 2), and at least one of the other two supporting arms (9, 11) being mounted in an articulated manner on the housing (8), and there is no need to maintain parallelism between the axes of said rollers. <IMAGE>

IPC 1-7

D02G 1/08

IPC 8 full level

D01H 1/11 (2006.01); **D02G 1/04** (2006.01); **D02G 1/08** (2006.01)

CPC (source: EP US)

D01H 1/11 (2013.01 - EP US); **D02G 1/085** (2013.01 - EP US)

Cited by

CN107572314A

Designated contracting state (EPC)

CH DE ES GB IT LI

DOCDB simple family (publication)

EP 0305305 A1 19890301; **EP 0305305 B1 19910515**; DE 3862830 D1 19910620; FR 2619831 A1 19890303; FR 2619831 B1 19891124; JP S6468532 A 19890314; US 4910953 A 19900327

DOCDB simple family (application)

EP 88420289 A 19880825; DE 3862830 T 19880825; FR 8712175 A 19870828; JP 20456288 A 19880817; US 22243088 A 19880721