

Title (en)

DEVICE FOR MOUNTING ON THE RIDGE OF A PITCHED ROOF FOR SECURING MEANS FOR HOLDING A ROOF RIDGE TILE IN PLACE

Publication

EP 0306109 B1 19901205 (EN)

Application

EP 88201880 A 19880902

Priority

NL 8702097 A 19870904

Abstract (en)

[origin: EP0306109A1] The device comprises two strips (4), to be fixed with nails or screws, which are joined to a part situated in between in a manner such that the angular position of the strips can be altered by pivoting or bending with respect to the part situated in between, the joining means can be secured to the part situated in between. In order to promote ventilation of the gap between the underside of the roofing tiles (6) and the top face of the roof boards (1, 2) and to prevent leakage as a consequence of an incorrect position of the uppermost tile laths with respect to the vertical plane through the centre of the roof ridge tile (7), the strips (4) are provided with a tiling lath profile (3) or a securing device for securing a wooden tile lath, a flexible sealing strip (9) which can be brought into contact with an uppermost row of roofing tiles (6) being joined by means of one or more securing legs (10) to said device. The part situated in between is a securing bracket (5).

IPC 1-7

E04D 1/34; **E04D 1/36**; **E04D 13/16**

IPC 8 full level

E04D 1/34 (2006.01); **E04D 1/36** (2006.01); **E04D 13/16** (2006.01); **E04D 13/17** (2006.01)

CPC (source: EP US)

E04D 1/3402 (2013.01 - EP US); **E04D 1/36** (2013.01 - EP); **E04D 13/174** (2013.01 - EP)

Cited by

DE4120829A1; AT401186B; EP0574036A1; JP2022069884A; GB2352257A; GB2352257B; GB2275064A; GB2275064B; DE4307982A1; EP2317024A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI LU NL

DOCDB simple family (publication)

EP 0306109 A1 19890308; **EP 0306109 B1 19901205**; AT E58944 T1 19901215; DE 3861230 D1 19910117; ES 2018877 B3 19910516

DOCDB simple family (application)

EP 88201880 A 19880902; AT 88201880 T 19880902; DE 3861230 T 19880902; ES 88201880 T 19880902