

Title (en)
IGNITION TRANSMISSION CHARGE FOR A PROPELLANT CHARGE

Publication
EP 0306616 A3 19900711 (DE)

Application
EP 88107278 A 19880506

Priority
DE 3730530 A 19870911

Abstract (en)
[origin: EP0306616A2] Hitherto known ignition transmission charges can be used to only a restricted extent because of their impact sensitivity to extreme loads such as occur as a result of acceleration processes during the feed of propellant-charge modules in high-calibre mortars, preferably guns. The new ignition transmission charge will withstand extreme impact loads and, furthermore, guarantee a likewise advantageous full ignition, and the supporting tube encasing the ignition charge will contribute to increasing the energy balance. <??>For this purpose, the ignition transmission charge 1 for a propellant charge 16 arranged in a propellant-charge module 14 consists of a high-energy propellant-charge powder with a heat quantity of 3 kJ/g to 4.5 kJ/g and a supporting tube 2 encasing the ignition transmission charge and consisting of normal compression-moulded propellant-charge powder. The ignition transmission charge 1 and supporting tube 2 are coaxially arranged mirror-symmetrically and rotationally symmetrically inside the propellant-charge module 14 and form at least one free ignition channel 17. The ignition transmission charge 1 can, for example, be connected as an extruded tube 4 to the supporting tube 2 or be designed as a foil adhesively bondable to the inner face of the supporting tube or, for example, be injected directly onto the inner face of the supporting tube 2. To achieve a higher ignition sensitivity, the inner face of the ignition transmission charge 1 is provided, for example, with longitudinal or transverse grooves. By means of this connection together with the supporting tube 2, the ignition transmission charge, in a layer thickness s of between 1 mm and 10 mm set in relation to the diameter and length of the ignition channel 17, withstands extreme impact loads during the feed of propellant-charge modules. <IMAGE>

IPC 1-7
F42C 19/08; F42B 5/38

IPC 8 full level
C06C 9/00 (2006.01); **F42B 5/38** (2006.01); **F42C 19/08** (2006.01)

CPC (source: EP US)
C06C 9/00 (2013.01 - EP US); **F42B 5/38** (2013.01 - EP US); **F42C 19/085** (2013.01 - EP US)

Citation (search report)
• [AD] DE 3432291 A1 19860313 - RHEINMETALL GMBH [DE]
• [A] GB 807499 A 19590114 - DU PONT
• [A] DE 3113406 A1 19821216 - BUNDESREP DEUTSCHLAND [DE]
• [A] GB 1177858 A 19700114 - ASAHI CHEMICAL IND [JP]

Cited by
CN111689824A; DE4041611A1; FR2683626A1; EP0952130A1; DE19604655A1; DE19604655C2; EP0949224A1; FR2776656A1; US6368434B1; EP0580017A1; EP0718591A2

Designated contracting state (EPC)
DE FR GB IT NL

DOCDB simple family (publication)
EP 0306616 A2 19890315; EP 0306616 A3 19900711; EP 0306616 B1 19920729; DE 3730530 A1 19890323; DE 3873227 D1 19920903; US 4922823 A 19900508

DOCDB simple family (application)
EP 88107278 A 19880506; DE 3730530 A 19870911; DE 3873227 T 19880506; US 23917488 A 19880831