

Title (en)

ELECTROMAGNETIC TRIP DEVICE FOR A LOW-VOLTAGE CIRCUIT BREAKER

Publication

EP 0309383 B1 19930428 (DE)

Application

EP 88730202 A 19880906

Priority

DE 3732256 A 19870922

Abstract (en)

[origin: EP0309383A1] It is intended to reduce the outlay required for the production of coils for electromagnetic trip devices. The coil (30) of an electromagnetic trip device (8) consists of a flexible, multi-wire conductor (cable 41), which, because of its flexibility, can be processed manually or by means of a manipulator. There is hence no requirement for the use of winding machines. In addition, components (10, 12) carrying the current path of a switching device (1) onwards can be connected to the ends of a coil conductor even before the coil (30) is wound. A sleeve body absorbs electrodynamic forces which result from short-circuit currents and stress the coil electrodynamically. Low-voltage switching device of compact construction (MCCB). <IMAGE>

IPC 1-7

H01H 71/24

IPC 8 full level

H01H 71/24 (2006.01)

CPC (source: EP)

H01H 71/2481 (2013.01); **H01H 71/2472** (2013.01)

Cited by

US7091811B2; DE4202122A1

Designated contracting state (EPC)

DE FR IT

DOCDB simple family (publication)

EP 0309383 A1 19890329; **EP 0309383 B1 19930428**; DE 3732256 A1 19890406; DE 3880604 D1 19930603

DOCDB simple family (application)

EP 88730202 A 19880906; DE 3732256 A 19870922; DE 3880604 T 19880906