

Title (en)
MULTIPLE CONTACT PIN SUPPORT FOR LOW-VOLTAGE INSTALLATIONS

Publication
EP 0310832 A3 19900425 (DE)

Application
EP 88115094 A 19880915

Priority
CH 373687 A 19870925

Abstract (en)
[origin: EP0310832A2] The multicontact pin holder of a modular connector for telephone or low-current installations has a means of insulation piercing wiring which comprises at least one pivoting cover (3), which can be pressed down onto the body (2) of the contact pin holder (1) and from which there project compression ribs (4) on the contact side, which, when the cover (3) is pressed down onto the body (2), penetrate into its wire insertion slots (5) and press the inserted wires into the insertion piercing devices (6) of the contact pins (7). In this way it is possible to carry out solder-free insulation piercing wiring rapidly, safely and absolutely without problems. <IMAGE>

IPC 1-7
H01R 4/24

IPC 8 full level
H01R 4/24 (2006.01)

CPC (source: EP)
H01R 4/2491 (2013.01)

Citation (search report)
• [X] US 4533199 A 19850806 - FELDBERG LEONARD [US]
• [Y] FR 2323245 A1 19770401 - AMP INC [US]
• [Y] FR 2575609 A1 19860704 - NOZICK JACQUES [FR]
• [Y] EP 0228723 A2 19870715 - REED DEVICES INC [US]

Cited by
EP0427132A3; EP1282203A3; US5154632A; DE19700600A1; DE19700600C2; FR2730096A1; US5681182A; AU678743B2; US5762518A; EP0671780A1; US5662493A; CN1045846C; US7137845B2

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0310832 A2 19890412; EP 0310832 A3 19900425; EP 0310832 B1 19940413; CH 674597 A5 19900615; DE 3889055 D1 19940519

DOCDB simple family (application)
EP 88115094 A 19880915; CH 373687 A 19870925; DE 3889055 T 19880915