

Title (en)

METHOD AND DEVICE FOR REPLACING ROVING BOBBINS IN A TEXTILE MACHINE

Publication

EP 0311862 B1 19920513 (DE)

Application

EP 88116282 A 19881001

Priority

CH 401787 A 19871014

Abstract (en)

[origin: EP0311862A1] Carriers 20 equipped with roving bobbins 14 and located on a suspended transport track 9 are introduced into the creel 5 of a spinning machine either from one longitudinal side or from both longitudinal sides of the machine, with the direction of the longitudinal axis 30 of each carrier being changed. <IMAGE>

IPC 1-7

D01H 9/00; **D01H 9/18**

IPC 8 full level

D01H 9/04 (2006.01); **D01H 9/00** (2006.01); **D01H 9/18** (2006.01)

CPC (source: EP KR US)

D01G 27/00 (2013.01 - KR); **D01H 9/005** (2013.01 - EP US); **D01H 9/182** (2013.01 - EP US)

Cited by

EP0544976A3; EP0421192A1; DE4000419A1; FR2728277A1; US6038846A; CN1080333C; DE19502586A1; EP0392482A3; US5697205A; CN1060828C; EP0457361A1; EP0329965A3; EP0392482A2; WO9012133A3; WO2008071346A1; WO9817849A1; WO9201098A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI NL SE

DOCDB simple family (publication)

EP 0311862 A1 19890419; **EP 0311862 B1 19920513**; AT E76121 T1 19920515; CN 1032557 A 19890426; DE 3871068 D1 19920617; ES 2032919 T3 19930301; GR 3005330 T3 19930524; JP 2641920 B2 19970820; JP H01124639 A 19890517; KR 890006880 A 19890616; TR 23484 A 19900131; US 4999988 A 19910319

DOCDB simple family (application)

EP 88116282 A 19881001; AT 88116282 T 19881001; CN 88107204 A 19881013; DE 3871068 T 19881001; ES 88116282 T 19881001; GR 920401665 T 19920731; JP 25502688 A 19881012; KR 880013369 A 19881013; TR 72888 A 19881013; US 52770890 A 19900521