

Title (en)

Ferrule and method for terminating a flexible coaxial cable.

Title (de)

Schraubenring und Methode, um ein flexibles Koaxialkabel anzuschliessen.

Title (fr)

Bague filetée et méthode pour raccorder un câble flexible coaxial.

Publication

EP 0313186 A2 19890426 (EN)

Application

EP 88306095 A 19880704

Priority

US 11291087 A 19871023

Abstract (en)

A ferrule for use in terminating a flexible microwave coaxial cable with a standard connector, comprises a rigid metal tube having tubular sections (4,5) of stepped diameter, fitting respectively over the jacket (1) and the exposed metallic shield (2) of the cable and secured to said jacket and/or said shield. A final tubular section (12) can be provided to fit over a central conductor (3) of the cable, this final section being insulated from the remainder of the ferrule.

IPC 1-7

H01R 17/12

IPC 8 full level

H01R 9/05 (2006.01); **H01R 13/646** (2011.01)

CPC (source: EP)

H01R 24/40 (2013.01); **H01R 2103/00** (2013.01)

Cited by

US11742624B2; EP0670610A3; FR2691844A1; FR2671434A1; US2022131322A1; DE19854451A1; DE19854451C2; DE4128722A1; DE19854504C1; CN102918714A; EP2565987A4; US9008739B2

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0313186 A2 19890426; **EP 0313186 A3 19900425**; AU 1461788 A 19890427; DK 577888 A 19890424; DK 577888 D0 19881017; FI 884829 A0 19881019; FI 884829 A 19890424; GB 2211674 A 19890705; GB 8815835 D0 19880810; JP H01130485 A 19890523; NO 883172 D0 19880715; NO 883172 L 19890424; PT 88112 A 19890731

DOCDB simple family (application)

EP 88306095 A 19880704; AU 1461788 A 19880414; DK 577888 A 19881017; FI 884829 A 19881019; GB 8815835 A 19880704; JP 22629988 A 19880909; NO 883172 A 19880715; PT 8811288 A 19880727