

Title (en)
THERMAL TRANSFER MATERIAL

Publication
EP 0313355 A3 19890913 (EN)

Application
EP 88309866 A 19881020

Priority
JP 26373187 A 19871021

Abstract (en)
[origin: EP0313355A2] A thermal transfer material comprising a support and at least a first ink layer and a second ink layer disposed in the order named on the support, wherein the adhesion strength F1 between the support and the first ink layer and the adhesion strength F2 between the first and second ink layers satisfy the relation of $F1 > F2$ at 90 DEG C. The thermal transfer material also provides a peeling strength of 1 - 5 g/cm at 90 DEG C. Two color recording is effected by superposing the thermal transfer material on plain paper, applying a pattern of heat and separating the thermal transfer material from the paper while changing the time from heating until the separation, i.e., temperature at the time of separation. Sharp edge-cutting of the heated portion and the selective transferability of the second ink layer are ensured by the definition of the peeling strength.

IPC 1-7
B41M 5/26

IPC 8 full level
B41M 5/382 (2006.01); **B41M 5/26** (2006.01); **B41M 5/40** (2006.01)

CPC (source: EP)
B41M 5/38228 (2013.01)

Citation (search report)
• [AD] EP 0208385 A2 19870114 - CANON KK [JP]
• [A] PATENT ABSTRACTS OF JAPAN, vol. 10, no. 10 (M-446)[2067], 16th January 1986; & JP-A-60 172 588 (NIPPON VICTOR K.K.) 06-09-1985
• [A] PATENT ABSTRACTS OF JAPAN, vol. 9, no. 264 (M-423)[1987], 22nd October 1985; & JP-A-60 110 495 (SANYO DENKI K.K.) 15-06-1985
• [A] PATENT ABSTRACTS OF JAPAN, vol. 8, no. 164 (M-313)[1601], 28th July 1984; & JP-A-59 59 493 (FUJITSU K.K.) 05-04-1984

Cited by
EP1228893A3; EP0539001A1

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0313355 A2 19890426; EP 0313355 A3 19890913; JP H01108089 A 19890425

DOCDB simple family (application)
EP 88309866 A 19881020; JP 26373187 A 19871021