

Title (en)
METHOD OF FASTENING AN ELEMENT

Publication
EP 0313866 A3 19910605 (DE)

Application
EP 88116283 A 19881001

Priority
AT 286187 A 19871030

Abstract (en)
[origin: EP0313866A2] The method is used for fastening an element to the upper side of a ski by means of at least one projection which is provided on the underside of the element and can be brought into engagement with at least one recess formed on/in the upper side of the ski. The length of the (each) projection (14-64) and the depth of the (each) recess (1a) are greater than the thickness of the upper wall of the body (1c) of the ski (1), each recess being formed by a borehole (1a) in the ski (1), which borehole is machined to extend into the core (1d) of the ski (1). In this case, the (each) projection (14-64) is inserted by means of at least one catch surface (14f-64f) with a press fit into the core (1d) of the associated borehole (1a). The invention also relates to an element which is suitable for applying the method. <IMAGE>

IPC 1-7
A63C 9/00

IPC 8 full level
A63C 11/26 (2006.01)

CPC (source: EP)
A63C 5/128 (2013.01); **A63C 11/26** (2013.01)

Citation (search report)
• [Y] FR 2595579 A1 19870918 - SALOMON SA [FR], et al
• [Y] DE 2107032 A1 19720914 - WESTFAELISCHE METALL INDUSTRIE
• [A] FR 2208692 A1 19740628 - SALOMON GEORGES P J [FR]
• [A] FR 2552672 A1 19850405 - SALOMON & FILS F [FR]
• [A] DE 1054786 C

Cited by
EP1161972A3; DE112004000162B4; EP1380323A1; US7503578B2; WO2004007036A1

Designated contracting state (EPC)
CH DE FR LI

DOCDB simple family (publication)
EP 0313866 A2 19890503; EP 0313866 A3 19910605; EP 0313866 B1 19941207; AT 399284 B 19950425; AT A286187 A 19890415; DE 3852372 D1 19950119; NO 169104 B 19920203; NO 169104 C 19920513; NO 884824 D0 19881028; NO 884824 L 19890502

DOCDB simple family (application)
EP 88116283 A 19881001; AT 286187 A 19871030; DE 3852372 T 19881001; NO 884824 A 19881028