

Title (en)
Sealing system for glazed roofs and glazed walls

Title (de)
Abdichtsystem für Glasdächer und Glaswände

Title (fr)
Système d'étanchéité pour un toit vitré ou un mur vitré

Publication
EP 0314052 B2 19960207 (DE)

Application
EP 88117712 A 19881025

Priority
DE 3736305 A 19871027

Abstract (en)
[origin: EP0314052A1] Water penetrating through leakage points in a glazed roof is to be caught and carried off not in appropriately shaped profiles (1, 2) of the supporting structure, but in an elastic distance profile (3) laid between these profiles (1, 2) and the glass panes (15). For this purpose, the distance profile (3) is divided below its bearing surfaces (6) into a lower (4) and an upper layer (5), and extending parallel to the bearing surface (6) is a projection (7), which is adjoined, in a variant (3a) of the distance profile (3) for the rafters (1), by the lower layer (4) and, in a variant (3b) of the distance profile (3) for the purlins (2), by the upper layer (5). This makes it possible, at the junctions of the purlins (2) with the rafters (1), to cut out or cut off the distance profiles (3) in such a way that they can be laid in an overlapping arrangement and the distance profile (3b) on the purlin (2) forms a conduit leading into the distance profile (3a) on the rafter (1). The distance profile (3) laid on the rafters (1) extends continuously from top to bottom and also beyond the bottom edge of the roof. <IMAGE>

IPC 1-7
E04D 3/08

IPC 8 full level
E04D 3/08 (2006.01)

CPC (source: EP)
E04D 3/08 (2013.01); **E04D 2003/0831** (2013.01); **E04D 2003/0837** (2013.01); **E04D 2003/085** (2013.01); **E04D 2003/0868** (2013.01); **E04D 2003/0893** (2013.01)

Cited by
EP0710750A3; DE19624629C1; EP0414105A1; EP1030132A1; FR2790022A1; FR2669357A1

Designated contracting state (EPC)
BE CH DE FR LI LU NL

DOCDB simple family (publication)
EP 0314052 A1 19890503; EP 0314052 B1 19920108; EP 0314052 B2 19960207; DE 3736305 A1 19890511; DE 3867592 D1 19920220

DOCDB simple family (application)
EP 88117712 A 19881025; DE 3736305 A 19871027; DE 3867592 T 19881025