

Title (en)
DISPENSER FOR PASTY PRODUCTS

Publication
EP 0315077 B1 19930811 (DE)

Application
EP 88118019 A 19881028

Priority
DE 3737832 A 19871106

Abstract (en)
[origin: JPH01153476A] PURPOSE: To accurately dispense the products in a desired position by mounting a pump chamber and a stripe chamber of a dispensing unit radially adjacent one another, and not comprising a valve which can freely communicate with the container cavity. CONSTITUTION: When a closing cap 28 is removed, and an operational cap 13 is pushed down, a projection 25 of the operational cap 13 pushes an operational finger 23, and a closing portion 21 is pivotally moved outwardly. Simultaneously, the pressure generated by the downward motion of a piston 10 and kept by an extension spring of a follower piston 4, dispenses the toothpaste in a container 2 through an inlet opening 17' of a first nozzle body 17. Further the rise of pressure is generated on the boundary between the toothpaste and the colored base in a stripe chamber 6, and the moved toothpaste is flown through the first nozzle body 17, so that a limited amount of colored paste is flown through an opening 18 to be placed on a circumferential portion of the toothpaste body in the dispensing passage 29 by the resulting differential pressure.

IPC 1-7
B65D 47/34

IPC 8 full level
B05B 11/00 (2006.01); **B65D 47/34** (2006.01); **B65D 83/00** (2006.01); **B65D 83/76** (2006.01)

CPC (source: EP US)
B05B 11/1053 (2023.01 - EP US); **B65D 83/0033** (2013.01 - EP US)

Designated contracting state (EPC)
AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
EP 0315077 A1 19890510; EP 0315077 B1 19930811; AT E92874 T1 19930815; DE 3737832 A1 19890518; DE 3883153 D1 19930916; ES 2045060 T3 19940116; JP H01153476 A 19890615; US 4856679 A 19890815

DOCDB simple family (application)
EP 88118019 A 19881028; AT 88118019 T 19881028; DE 3737832 A 19871106; DE 3883153 T 19881028; ES 88118019 T 19881028; JP 27461488 A 19881101; US 15140088 A 19880202