

Title (en)
SKI BRAKE

Publication
EP 0316311 B1 19920812 (DE)

Application
EP 87903693 A 19870518

Priority
EP 8700261 W 19870518

Abstract (en)
[origin: WO8809197A1] A ski brake (1) has two wire brake arms (7) pivotally mounted on a base plate (2), the terminal sections (7d) of the said arms being connected through a spring (8). The brake (1) is maintained in the operating position by an actuating pedal (5) arranged on the upper side of the ski, which is depressed against the force of at least one lifting spring (6). The free ends (7a) of the wire brake arms (7) pivot in the direction of the longitudinal axis of the ski (10). To improve the transmission of force from the base plate (2) to the wire brake arms (7) when the actuating pedal (5) is depressed, an intermediate element (a) consisting of a cylindrical sleeve (9a) connected to a projection (9b) is mounted in a hinged manner on the terminal sections (7d). In the operating position, the projection (9b) presses against a supporting surface (2f) of the base plate (2).

IPC 1-7
A63C 7/10

IPC 8 full level
A63C 7/10 (2006.01)

CPC (source: EP US)
A63C 7/104 (2013.01 - EP US)

Designated contracting state (EPC)
AT CH DE FR IT LI

DOCDB simple family (publication)
WO 8809197 A1 19881201; DE 3781158 D1 19920917; EP 0316311 A1 19890524; EP 0316311 B1 19920812; JP H01501043 A 19890413; US 4973072 A 19901127

DOCDB simple family (application)
EP 8700261 W 19870518; DE 3781158 T 19870518; EP 87903693 A 19870518; JP 50350887 A 19870518; US 30269489 A 19890117