Title (en)

FITTING FOR A CORNER CUPBOARD, IN PARTICULAR A KITCHEN CORNER CUPBOARD

Publication

EP 0317737 A3 19900117 (DE)

Application

EP 88116107 A 19880929

Priority

DE 8715598 U 19871125

Abstract (en)

[origin: EP0317737A2] The fitting for a corner cupboard, in particular a kitchen corner cupboard has a carousel, containing at least one shelf, having a rotatably mounted rotary column (3) and a two-leaved door (8, 9), which is connected to the rotary column (3) via a fitting linkage, the leaves (8, 9) of which door execute during opening and closing a folding-in or folding-out movement, which is symmetrical in relation to the angle bisector of the door corner, with a superimposed radial retraction end extension movement and are held in the closed position by a spring device (37). Arranged between two parts (26, 28), which execute a movement relative to each other during the door movement, is a movement braking member (40), the braking force of which is directed counter to the closing movement. <IMAGE>

IPC 1-7

A47B 49/00

IPC 8 full level

A47B 49/00 (2006.01)

CPC (source: EP)

A47B 49/006 (2013.01)

Citation (search report)

[AD] DE 3049114 C2 19850328

Cited by

EP0459189A1; DE19860241B4; DE202014104991U1; DE19518438C2; AT500212B1; EP1703058A3; EP1817979A1; DE202009014740U1; US7690739B2; EP1163863A1; DE202018103222U1; DE102019114644A1; EP1703058A2; EP1080668A1; DE202005022000U1

Designated contracting state (EPC)

AT DE FR GB IT SE

DOCDB simple family (publication)

EP 0317737 A2 19890531; ÉP 0317737 A3 19900117; EP 0317737 B1 19911204; AT E69934 T1 19911215; DE 3866681 D1 19920116; DE 8715598 U1 19880114

DOCDB simple family (application)

EP 88116107 A 19880929; AT 88116107 T 19880929; DE 3866681 T 19880929; DE 8715598 U 19871125