

Title (en)

METHOD FOR PRODUCING PROTECTED METAL BASES FOR AEROSOL VALVES AND THE LIKE

Publication

EP 0317865 A3 19890823 (EN)

Application

EP 88118963 A 19881114

Priority

IT 2274287 A 19871124

Abstract (en)

[origin: EP0317865A2] According to the method, after the metal base for the aerosol valve or the like has been formed by conventional methods from sheet metal, a layer of protective plastics material such as polyethylene or polypropylene is applied to at least one of its sides. This application can be done by known methods such as spraying or immersion. The metal base can be formed from unprotected steel which is tin-, nickel- or chromium-plated, or from varnished aluminium alloy. The plastics material is preferably applied differentially to obtain selectively different layers on the metal base, for example a greater thickness on the inside of its rim, this being the region where the base is clinched or otherwise fixed to the container.

IPC 1-7

B05D 7/14; B65D 83/14

IPC 8 full level

B05B 11/00 (2006.01); **B05D 7/14** (2006.01); **B65D 83/14** (2006.01)

CPC (source: EP)

B05B 11/1047 (2023.01); **B05D 7/14** (2013.01); **B65D 83/38** (2013.01)

Citation (search report)

- [X] WO 8401356 A1 19840412 - SEAQUIST VALVE CO [US]
- [X] WO 8302437 A1 19830721 - VALOIS VALVES AEROSOLS [FR]

Cited by

EP0875463A4; FR2823183A1; US6149892A; EP0875469A1; US6143277A; FR2779419A1; US6131566A; US7021503B2; US6978915B1; WO02081332A1; US8292121B2; US6524555B1; US6546928B1; US6253762B1; US6511652B1; US6511653B1; US6532955B1; US8227027B2; US8703306B2

Designated contracting state (EPC)

DE ES FR GB

DOCDB simple family (publication)

EP 0317865 A2 19890531; EP 0317865 A3 19890823; IT 1223451 B 19900919; IT 8722742 A0 19871124

DOCDB simple family (application)

EP 88118963 A 19881114; IT 2274287 A 19871124