

Title (en)

APPARATUS FOR AVOIDING DAMAGE TO MACHINES

Publication

EP 0318853 B1 19910821 (DE)

Application

EP 88119646 A 19881125

Priority

- DE 3740812 A 19871202
- DE 3822497 A 19880702

Abstract (en)

[origin: JPH01168453A] PURPOSE: To facilitate operation of a printing plant without interrupting web feed unnecessarily by actuating a web interrupter when a web is torn to cause an angular deflection of the web which may damage the printing plant. CONSTITUTION: In order to protect a printer against damage, a web interrupting means 5 is disposed between the final print unit 1 of a printer and a dryer 3. The web interrupting means 5 has a grasping jaw 6 and/or a knife 7 which acts upon displacement of a web 2 to grasp or cut off the web 2. A slot 9 for passing the web is located on the inlet side of an inlet slot 10. The web interrupting means 5 is also provided with a web tear detection switch 11 disposed closely to a cylinder 4 for displacing the web 2 when it is torn.

IPC 1-7

B41F 13/02; B65H 26/02

IPC 8 full level

B65H 26/00 (2006.01); **B41F 13/02** (2006.01); **B41F 33/06** (2006.01); **B41F 33/16** (2006.01); **B41F 33/18** (2006.01); **B65H 26/02** (2006.01)

CPC (source: EP US)

B41F 33/06 (2013.01 - EP US); **B41F 33/16** (2013.01 - EP US); **B41F 33/18** (2013.01 - EP US); **B65H 26/025** (2013.01 - EP US);
B41P 2233/21 (2013.01 - EP US)

Cited by

FR2673395A1; EP0442824A3; EP0525450A1; EP0563645A1; EP0703077A1; DE10222587A1; DE10222586A1; FR2761355A1; DE4219645A1;
DE3938478A1; US6761111B2

Designated contracting state (EPC)

CH DE ES FR GB IT LI SE

DOCDB simple family (publication)

EP 0318853 A2 19890607; EP 0318853 A3 19890920; EP 0318853 B1 19910821; DE 3822497 A1 19891019; DE 3864389 D1 19910926;
JP H01168453 A 19890703; US 4887532 A 19891219

DOCDB simple family (application)

EP 88119646 A 19881125; DE 3822497 A 19880702; DE 3864389 T 19881125; JP 29801888 A 19881125; US 27006488 A 19881114