

Title (en)
PIN CARRYING POWER TERMINAL BLOCK

Publication
EP 0320356 B1 19930421 (FR)

Application
EP 88403069 A 19881205

Priority
FR 8717291 A 19871211

Abstract (en)
[origin: EP0320356A1] The invention resides in the fact that the socket 37 is mounted so as to float in an opening 36 and in that the pin 25 is mounted in an opening 21 terminated by a bore 24 in which there is disposed a thick elastic sealing ring 32. Thus, when the two parts, male and female, are assembled, the sealing ring 32 comes to bear against the socket and elastically locks it in its housing. The invention is applicable to connectors used in aircraft. <IMAGE>

IPC 1-7
H01R 23/02

IPC 8 full level
B64D 47/00 (2006.01); **H01R 4/30** (2006.01); **H01R 9/24** (2006.01); **H01R 13/434** (2006.01); **H01R 13/629** (2006.01); **H01R 24/00** (2006.01)

CPC (source: EP)
H01R 13/6315 (2013.01); **H01R 13/6456** (2013.01); **H01R 24/20** (2013.01); **H01R 9/24** (2013.01); **H01R 24/28** (2013.01); **H01R 2107/00** (2013.01)

Cited by
KR20200034373A; FR3084211A1

Designated contracting state (EPC)
DE FR GB IT NL

DOCDB simple family (publication)
EP 0320356 A1 19890614; **EP 0320356 B1 19930421**; DE 3880452 D1 19930527; DE 3880452 T2 19930805; FR 2624657 A1 19890616; FR 2624657 B1 19900330

DOCDB simple family (application)
EP 88403069 A 19881205; DE 3880452 T 19881205; FR 8717291 A 19871211