

Title (en)
AXIAL PISTON PUMP

Publication
EP 0320822 B1 19910306 (DE)

Application
EP 88120650 A 19881209

Priority
DE 3743125 A 19871218

Abstract (en)
[origin: EP0320822A1] An axial piston pump (1) of constant or adjustable delivery with a two-part housing, that is one part (2) accommodating the pistons (12) and a connected part (3) through which the pressure duct (52) and the intake duct (51) extend, the intake duct (51) having an intake aperture (53) of enlarged cross-section compared to the pressure duct (52), is to be designed in such a way that it can be adjusted to what is respectively the other direction of delivery with little effort. This is achieved in that the connected part (3) can be attached to the housing part (2) in either of two positions, rotationally offset in relation to one another, essentially by 180° about the centre axis (4) of the axial piston machine (1).
<IMAGE>

IPC 1-7
F04B 1/20

IPC 8 full level
F04B 1/20 (2006.01)

CPC (source: EP US)
F04B 1/2042 (2013.01 - EP US)

Cited by
DE19643389C1; AU2018204390B2; EP0837241A2; DE102015212731A1; US10527029B2; WO2008071374A1; WO9601947A1; WO2014187545A1; WO2014187546A1

Designated contracting state (EPC)
DE FR GB IT SE

DOCDB simple family (publication)
EP 0320822 A1 19890621; EP 0320822 B1 19910306; EP 0320822 B2 19970129; DE 3743125 A1 19890706; DE 3861956 D1 19910411; JP 2554927 B2 19961120; JP H01200068 A 19890811; US 4934253 A 19900619

DOCDB simple family (application)
EP 88120650 A 19881209; DE 3743125 A 19871218; DE 3861956 T 19881209; JP 32029788 A 19881219; US 28362288 A 19881213