

Title (en)

FLUID DISPLACEMENT APPARATUS WITH A SPIRAL ELEMENT

Publication

**EP 0321781 B1 19920226 (DE)**

Application

**EP 88120414 A 19881207**

Priority

CH 498287 A 19871221

Abstract (en)

[origin: JPH01206101A] PURPOSE: To make distance fluctuation be compensated by connecting a guide eye to a disk-shaped rotor via fin and forming the fin as a tangential extension on an inlet-side end of one of spiral strips. CONSTITUTION: A guide eye 5 of an eccentric guiding arrangement 26, 27 is connected to a disk-shaped rotor 1 via fin 29 with it longitudinal direction tangentially extending toward a spiral and connected with an inlet-side end of a spiral-shaped strip 3. Consequently, since a high rigid in the tangential direction and a high elasticity in a radial direction can be obtained, a distance fluctuation generated between two working points can be compensated automatically.

IPC 1-7

**F01C 1/02**

IPC 8 full level

**F15B 15/12** (2006.01); **F01C 1/02** (2006.01); **F04C 18/02** (2006.01)

CPC (source: EP US)

**F01C 1/0223** (2013.01 - EP US)

Cited by

EP0547491A1; EP0545188A1; EP0545190A1; US5322426A; EP0899423A1; EP0560009A1; DE4207984A1; EP0463370A3

Designated contracting state (EPC)

AT CH DE ES FR GB IT LI NL

DOCDB simple family (publication)

**EP 0321781 A1 19890628**; **EP 0321781 B1 19920226**; AT E72878 T1 19920315; CH 673680 A5 19900330; DE 3868609 D1 19920402; ES 2028978 T3 19920716; JP 2758178 B2 19980528; JP H01206101 A 19890818; US 4950138 A 19900821

DOCDB simple family (application)

**EP 88120414 A 19881207**; AT 88120414 T 19881207; CH 498287 A 19871221; DE 3868609 T 19881207; ES 88120414 T 19881207; JP 31970888 A 19881220; US 28273788 A 19881212