

Title (en)
SOLID BOWL CENTRIFUGE

Publication
EP 0322516 A3 19900425 (DE)

Application
EP 88115690 A 19880923

Priority
DE 3744093 A 19871224

Abstract (en)
[origin: EP0322516A2] In a solid bowl centrifuge, in particular for separating media with different density or their mixtures and/or suspensions, which are difficult to separate into a comparatively lighter and at least one heavier phase, having a drum which is rotatably mounted on a shaft and forms in itself a settling basin, and having elements for feeding in the media to be separated and for discharging the separated phases, it is proposed that the discharge element (8) for the lighter phase (14) be led to an overflow (8a) on a drum end wall (16) and the discharge element (9) for the heavier phase (13) be constructed, starting from the lowest region (17) of the settling basin (3), with a conveying device (18) and be arranged so as to open into the discharge-side part of the hollow shaft (43b) of the expulsion body (6). In this arrangement, the conveying device (18) can be constructed as a compressed-air liquid syphon (37). <IMAGE>

IPC 1-7
B04B 1/20

IPC 8 full level
B04B 1/02 (2006.01); **B04B 1/20** (2006.01)

CPC (source: EP US)
B04B 1/20 (2013.01 - EP US); **B04B 2001/2083** (2013.01 - EP US); **B04B 2001/2091** (2013.01 - EP US)

Citation (search report)
• [A] EP 0237067 A2 19870916 - KRAUSS MAFFEI AG [DE]
• [A] US 4566873 A 19860128 - TODA TOSHIYUKI [JP]
• [A] DE 3335873 A1 19850221 - KLOECKNER HUMBOLDT DEUTZ AG [DE]
• [AD] DE 3317047 A1 19840105 - LEIPZIG CHEMIEANLAGEN [DD]

Cited by
CN110388465A

Designated contracting state (EPC)
DE FR GB IT NL SE

DOCDB simple family (publication)
EP 0322516 A2 19890705; EP 0322516 A3 19900425; DE 3744093 A1 19890713; JP H01203063 A 19890815; US 4898571 A 19900206

DOCDB simple family (application)
EP 88115690 A 19880923; DE 3744093 A 19871224; JP 32380988 A 19881223; US 27797888 A 19881130