

Title (en)  
CONTACT MEMBER

Publication  
**EP 0323574 B1 19930203 (DE)**

Application  
**EP 88120009 A 19881130**

Priority  
DE 8716917 U 19871223

Abstract (en)  
[origin: EP0323574A1] The U-shaped bent contact member (1) has insulation-perforating terminals on the ends of the side limbs for connection to incoming and outgoing connecting wires (2). Two contact springs (5) are torn off in the manner of fins from the base of the contact member (1) along its longitudinal edges, from the opposite direction, and are bent in the direction of the side limbs. The contact springs form a contact point for the connection of a protection plug. <IMAGE>

IPC 1-7  
**H01R 4/24**

IPC 8 full level  
**H01R 4/24** (2006.01); **H01R 4/48** (2006.01)

CPC (source: EP)  
**H01R 4/48** (2013.01)

Cited by  
EP0678932A1; AU670899B2

Designated contracting state (EPC)  
AT BE CH DE FR GB IT LI NL

DOCDB simple family (publication)  
**EP 0323574 A1 19890712; EP 0323574 B1 19930203**; AT E85463 T1 19930215; AU 2752788 A 19890629; AU 613132 B2 19910725;  
DE 3878207 D1 19930318; DE 8716917 U1 19880218; FI 885946 A 19890624; FI 94004 B 19950315; FI 94004 C 19950626;  
NO 172878 B 19930607; NO 172878 C 19930915; NO 885739 D0 19881223; NO 885739 L 19890626; PT 8872 T 19940531;  
PT 8872 U 19960229; PT 89331 A 19890914

DOCDB simple family (application)  
**EP 88120009 A 19881130**; AT 88120009 T 19881130; AU 2752788 A 19881222; DE 3878207 T 19881130; DE 8716917 U 19871223;  
FI 885946 A 19881222; NO 885739 A 19881223; PT 887293 U 19930824; PT 8933188 A 19881222