

Title (en)
SAFETY ARMATURE FOR DOOR LOCKS PROVIDED WITH A PROFILE LOCKING CYLINDER

Publication
EP 0323575 A3 19910206 (DE)

Application
EP 88120059 A 19881201

Priority
DE 8800037 U 19880105

Abstract (en)
[origin: EP0323575A2] Safety fitting (21) for door locks provided with a profiled lock cylinder (1), with a recess (4) leaving free at least the end face (2) of the cylinder housing (10) and belonging to a door plate (5) which has a plate portion (7) engaging in front of the outer contour profile of the cylinder housing (10) and therefore preventing the latter from being forcibly pulled out. To improve a safety fitting (21) of the type mentioned in the introduction, in such a way as to prevent the lock cylinder (1) from being forcibly pulled out, without actions or measures on the key or on the door plate (5), it is so designed that the end face (2) of the cylinder housing (10) is arranged approximately flush with the outer face (8) of the door plate (5), and that the cylinder housing (10) has at least one circumferential recess (9) which is located on the end face and is of limited longitudinal depth and into which the plate portion (7) engages. <IMAGE>

IPC 1-7
E05B 17/18

IPC 8 full level
E05B 15/02 (2006.01); **E05B 17/18** (2006.01)

CPC (source: EP)
E05B 15/02 (2013.01)

Citation (search report)
• [A] DE 2820742 A1 19791122 - KARRENBURG FA WILHELM
• [A] DE 8419098 U1 19840920
• [XP] DE 8800037 U1 19880303

Cited by
AU628014B3; WO03073385A3

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI LU NL

DOCDB simple family (publication)
EP 0323575 A2 19890712; EP 0323575 A3 19910206; EP 0323575 B1 19931013; AT E95876 T1 19931015; DE 3884931 D1 19931118; DE 8800037 U1 19880303

DOCDB simple family (application)
EP 88120059 A 19881201; AT 88120059 T 19881201; DE 3884931 T 19881201; DE 8800037 U 19880105