

Title (en)
LIGHT FIXTURE SECURED UNDER TENSION BETWEEN FLOOR AND CEILING

Publication
EP 0324176 B1 19930609 (DE)

Application
EP 88121831 A 19881229

Priority
DE 3800792 A 19880114

Abstract (en)
[origin: EP0324176A2] The present invention relates to a light fixture which can be secured under tension between floor and ceiling of a room (so-called tensioned light fixture). The light fixture has a pair of rod-shaped conductor rails (42, 43), which conduct low voltage and are not insulated over the greater part of the length. These conductor rails (42, 43) are accommodated in the lower section by a tubular lower part (40) and in the upper section by a tubular upper part (10). The tubular upper part (10) of the light fixture can be displaced in the direction of the arrow (54) towards the conductor rails (42, 43) against the force of a spring, the conductor rails being guided in the upper part of the light fixture. Lamps (53) can be clamped to the low-voltage current rails (42, 43) in any position with the aid of fittings (52). <IMAGE>

IPC 1-7
F21V 21/10; F21V 21/34

IPC 8 full level
F21S 6/00 (2006.01); **F21V 21/02** (2006.01); **F21V 21/10** (2006.01); **F21V 21/13** (2006.01); **F21V 21/34** (2006.01); **F21V 21/35** (2006.01); **F21Y 101/00** (2006.01)

CPC (source: EP)
F21V 21/13 (2013.01); **F21V 21/35** (2013.01)

Cited by
GB2416200A; EP0551602A1; GB2385262A; WO2007131644A1

Designated contracting state (EPC)
AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
EP 0324176 A2 19890719; EP 0324176 A3 19900404; EP 0324176 B1 19930609; AT E90434 T1 19930615; DE 3800792 A1 19890727; DE 3881672 D1 19930715; ES 2042707 T3 19931216

DOCDB simple family (application)
EP 88121831 A 19881229; AT 88121831 T 19881229; DE 3800792 A 19880114; DE 3881672 T 19881229; ES 88121831 T 19881229