

Title (en)
ELECTRICAL CONNECTOR

Publication
EP 0324268 A3 19900131 (EN)

Application
EP 88312245 A 19881222

Priority
• JP 15950988 U 19881209
• JP 19602187 U 19871225

Abstract (en)
[origin: EP0324268A2] An electrical connector is disclosed including a housing (10) having a plurality of cavities (11) which support electrical contacts (20) therein. Each electrical contact (20) has a bent distal end portion (21) extending from the outside of the cavity (11) into the cavity (11). The distal end portion (21) is biased. The distal end portion (21) of the contact (20) is inserted through an engaging hold (12) formed at the upper portion of the peripheral wall of the housing. The distal end portion (21) of the contact (20) is placed in electrical connection with a portion of a conductive element which is inserted into the housing cavity (11).

IPC 1-7
H01R 13/11; **H01R 13/42**

IPC 8 full level
H01R 12/04 (2006.01); **H01R 12/22** (2006.01); **H01R 13/11** (2006.01); **H01R 13/40** (2006.01); **H01R 24/00** (2006.01)

CPC (source: EP)
H01R 13/11 (2013.01)

Citation (search report)
• [X] EP 0233742 A2 19870826 - DU PONT [US]
• [Y] US 4647136 A 19870303 - KINOSHITA YOSHICHIKA [JP], et al
• [X] PATENT ABSTRACTS OF JAPAN vol. 8, no. 111 (E-246)(1548) 24 May 1984, & JP 59027555 A (TAIKOU DENKI K.K.) 14 February 1984,

Designated contracting state (EPC)
BE CH DE ES FR GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0324268 A2 19890719; **EP 0324268 A3 19900131**; JP H01166984 U 19891122; JP H089902 Y2 19960321

DOCDB simple family (application)
EP 88312245 A 19881222; JP 15950988 U 19881209