

Title (en)

DISPENSER FOR LIQUIDS OR PASTES PRESSURISED BY DEFORMING A RESILIENT CONTAINER PRIOR TO ITS FILLING

Publication

EP 0324289 B1 19920506 (FR)

Application

EP 88402681 A 19881024

Priority

FR 8800122 A 19880108

Abstract (en)

[origin: EP0324289A1] In order to dispense a liquid or pasty product, it is advantageous to package it under pressure, in the absence of air, inside a container (1) which is closed off hermetically by a valve (2). A convenient way of placing it under pressure therefore consists in using an elastic container (1) which has been previously deformed so that its walls (10), seeking to re-assume their natural shape (in broken lines), exert a force on the product. <??>The present invention has recourse to mechanical means for imposing this deformation. Thus, the container (1) may be filled with product at atmospheric pressure. It also consists of a single casing whose shape respects the display conditions peculiar to the market for this type of dispenser and lends itself to easy handling. Finally, when it is provided with a valve (2) of the precompression-pump-type, up to 95% of the product initially contained in the container (1) can be used up. <IMAGE>

IPC 1-7

B65B 3/04; **B65D 83/00**; **B67C 3/04**

IPC 8 full level

B65D 35/00 (2006.01); **B65B 3/04** (2006.01); **B65D 83/00** (2006.01); **B67C 3/04** (2006.01)

CPC (source: EP US)

B65D 83/0061 (2013.01 - EP US)

Cited by

FR2668119A2; US5237797A; FR2653744A1; EP0509179A1; US10913836B2; WO2014111939A3; US9758641B2; US10519297B2; US10239682B2; US10934076B2; US9409698B2; US10683159B2

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0324289 A1 19890719; **EP 0324289 B1 19920506**; AT E75691 T1 19920515; DE 3870847 D1 19920611; FR 2625729 A1 19890713; FR 2625729 B1 19900817; JP 2571710 B2 19970116; JP H01254560 A 19891011; US 4984712 A 19910115

DOCDB simple family (application)

EP 88402681 A 19881024; AT 88402681 T 19881024; DE 3870847 T 19881024; FR 8800122 A 19880108; JP 56989 A 19890106; US 29391589 A 19890106