

Title (en)

APPARATUS FOR CUTTING AND ATTACHING METAL STRIP TO A COILING REEL

Publication

EP 0325306 B1 19910424 (DE)

Application

EP 89104898 A 19870725

Priority

DE 3626638 A 19860806

Abstract (en)

[origin: US4770227A] The invention relates to an apparatus for the production of cast metal strip of amorphous and/or compact grained structures. To enable the strip to be coiled on reels at high strip speeds, the strip 6 is guided at the outlet of the casting apparatus 1-6 having a casting wheel 4 over a first and second strip guide channel. The first strip guide channel is formed by at least one cooling wheel 9, 11 and a guide wall 10, 12 disposed concentrically of the cylindrical surface of the cooling wheel 9, 11. By means of a cooling medium the strip is forced against the cylindrical surface of the cooling wheel 9, 11 and thereby intensively cooled at a high conveying speed and without tensile stress. When it leaves the or each cooling wheel 9, 11 the strip 6 is strong enough to pass freely guided through the perpendicularly disposed second guide channel 14. Disposed at the outlet of the guide channel 14 is a gripping device 16 which seizes the strip 6, so that the strip guide channel 14 is no longer required for guidance and is therefore removed. By means of a contact pressure and parting device 24 movable against the strip 6, the strip can be forced with uninterrupted conveying against a coiling reel 19, 20 and be glued on by means of an adhesive coating. Preferably a roller device 29 to 34 is associated with the cooling wheel 11 in the first guide channel.

IPC 1-7

B22D 11/06; B65H 19/28

IPC 8 full level

B22D 11/06 (2006.01); **B65H 19/28** (2006.01)

CPC (source: EP US)

B22D 11/0694 (2013.01 - EP US); **B65H 19/28** (2013.01 - EP US); **B65H 2701/173** (2013.01 - EP US); **Y10S 242/909** (2013.01 - EP US)

Cited by

EP0440035A1; US5184788A

Designated contracting state (EPC)

CH DE FR GB LI

DOCDB simple family (publication)

EP 0325306 A2 19890726; EP 0325306 A3 19890830; EP 0325306 B1 19910424; DE 3626638 A1 19880218; DE 3626638 C2 19880804; DE 3761800 D1 19900412; DE 3769660 D1 19910529; EP 0255674 A2 19880210; EP 0255674 A3 19880831; EP 0255674 B1 19900307; JP H038543 A 19910116; JP H0429457 B2 19920519; JP S6372451 A 19880402; US 4770227 A 19880913

DOCDB simple family (application)

EP 89104898 A 19870725; DE 3626638 A 19860806; DE 3761800 T 19870725; DE 3769660 T 19870725; EP 87110817 A 19870725; JP 12430190 A 19900516; JP 19455487 A 19870805; US 8199187 A 19870805