

Title (en)  
SABOT WITH A DRIVING BELT

Publication  
**EP 0326653 B1 19911030 (DE)**

Application  
**EP 88117169 A 19881015**

Priority  
DE 3802857 A 19880201

Abstract (en)  
[origin: EP0326653A1] The invention relates to a jettisonable sabot with driving belt for a subcalibre fin-stabilised projectile. During the operation of detaching the sabot segments, considerable faults can occur on the projectile body, with reduction of the accuracy of hit, as a result of an irregular tearing of the driving or holding belt. The present invention guarantees a uniform and simultaneous tearing of the driving belt 20 at the parting planes 14 and ensures a fault-free detachment of the individual sabot segments 23, 25. This is achieved by positive means 24 arranged on the underside of the driving belt 20 and intended for initiating the tearing and/or limiting the range of expansion of the driving belt 20 about the predetermined breaking point in the parting plane 14. <IMAGE>

IPC 1-7  
**F42B 14/06**

IPC 8 full level  
**F42B 14/02** (2006.01); **F42B 14/06** (2006.01)

CPC (source: EP)  
**F42B 14/02** (2013.01); **F42B 14/061** (2013.01)

Cited by  
EP2221576A3; KR101531427B1; EP0580511A1; FR2694081A1

Designated contracting state (EPC)  
CH DE FR GB IT LI NL SE

DOCDB simple family (publication)  
**EP 0326653 A1 19890809; EP 0326653 B1 19911030**; DE 3802857 A1 19890803; DE 3865961 D1 19911205; IL 88896 A0 19890815; JP H028700 A 19900112

DOCDB simple family (application)  
**EP 88117169 A 19881015**; DE 3802857 A 19880201; DE 3865961 T 19881015; IL 8889689 A 19890106; JP 1993089 A 19890131