

Title (en)

MAGNETIC SEAL FOR THE GAP BETWEEN A FLOOR AND A DOOR

Publication

**EP 0327840 A3 19890920 (DE)**

Application

**EP 89100745 A 19890118**

Priority

DE 3803673 A 19880206

Abstract (en)

[origin: EP0327840A2] The present invention relates to a magnetic seal for the gap between a floor and a door, comprising a threshold element (4) which can be mounted on the floor side, a counter-element (2) which can be mounted on the surface of the door leaf on the floor side, and a closing element (6) which moves under magnetic influence and consists of a strip which is hinged on the threshold side or door side in the vicinity of the closing surface of the door leaf and which is held in a horizontal position without magnetic influence when the door is open, whereas it is held in an oblique position by means of magnetic forces upon closing of the door, in which arrangement it rests against the element on the door leaf side or floor side. The magnetic seal according to the invention may be installed subsequently, which involves the threshold becoming extremely flat without sealing level being lost. <IMAGE>

IPC 1-7

**E06B 7/20**

IPC 8 full level

**E06B 7/20** (2006.01); **E06B 7/215** (2006.01); **E06B 7/23** (2006.01)

CPC (source: EP)

**E06B 7/20** (2013.01); **E06B 7/215** (2013.01); **E06B 7/2316** (2013.01)

Citation (search report)

- [AD] DE 3533782 A1 19870326 - FREY HARRY
- [A] DE 2312080 A1 19740912 - WARMBIER WERNER DIPL KFM
- [A] DE 900492 C 19531228 - HANS WILLI
- [XP] DE 8804428 U1 19880929

Cited by

DE4010994A1; GB2362178A; USD903902S; USD875969S; WO2014206525A1; US9874054B2; US8991101B2; US11085229B2; US10077593B2; US10801250B2; US11346145B1; US11346146B1; US8991100B2; US9371682B2; US10066433B2; US10407975B2; US10858881B2; US11193321B2

Designated contracting state (EPC)

FR IT NL

DOCDB simple family (publication)

**EP 0327840 A2 19890816**; **EP 0327840 A3 19890920**; DE 3803673 A1 19890817; DE 8816745 U1 19900705

DOCDB simple family (application)

**EP 89100745 A 19890118**; DE 3803673 A 19880206; DE 8816745 U 19880206