

Title (en)

TRANSPORTABLE ROUNDABOUT WITH AT LEAST TWO TURNTABLES PLACED STOREY-WISE

Publication

EP 0327942 B1 19920506 (DE)

Application

EP 89101709 A 19890201

Priority

- DE 8801883 U 19880212
- DE 8810076 U 19880806

Abstract (en)

[origin: EP0327942A2] The transportable, power-driven roundabout has at least two turntables (6, 7) which are arranged concentrically and storey-wise, rotate about a central mast (4) and are suspended via radial arms (8), arranged in the manner of spokes, on a rotating hub (5) arranged on the mast. In this case, at least one of the platforms (6, 7) has foldable or removable segments and the arms (8) are constructed as approximately L-shaped bent arms having a limb (8a) extending upwards from the hub (5) in the operating position and an adjoining limb (8b) which is approximately horizontal in the operating position. These arms are connected to the hub (5) so as to be swivellable in each case both vertically and horizontally. By this means, without substantial assembly work, the roundabout can be brought into a transport position with a small width which is permissible for road transport. <IMAGE>

IPC 1-7

A63G 1/00

IPC 8 full level

A63G 1/00 (2006.01)

CPC (source: EP US)

A63G 1/00 (2013.01 - EP US)

Cited by

FR2722109A1; BE1008680A3

Designated contracting state (EPC)

DE ES FR GB IT NL

DOCDB simple family (publication)

DE 8810076 U1 19881006; DE 58901292 D1 19920611; EP 0327942 A2 19890816; EP 0327942 A3 19900117; EP 0327942 B1 19920506; ES 2031289 T3 19921201; JP H01249084 A 19891004; JP H0755261 B2 19950614; US 4917374 A 19900417

DOCDB simple family (application)

DE 8810076 U 19880806; DE 58901292 T 19890201; EP 89101709 A 19890201; ES 89101709 T 19890201; JP 3091389 A 19890209; US 30959489 A 19890213