

Title (en)

HANGING DEVICE, IN PARTICULAR FOR HOSIERY

Publication

EP 0328490 B1 19920617 (DE)

Application

EP 89810111 A 19890210

Priority

CH 49688 A 19880211

Abstract (en)

[origin: EP0328490A2] The hanging device consists essentially of a rectangular tube (11), two end plates (12), the pins (43) of which project into the rectangular tube (11), and a number of hangers (13). The hangers (13) are inserted in insertion openings (15) of the rectangular tube (11) and can easily be swivelled from their normal position (N). A stabilising member in the form of a cylinder (33) is connected fixedly to the hanger (13). The stabilising part (33) rests on the edge (35) of the support. When the hanger (13) is swivelled, the stabilising member (33) causes the hanger to be pulled slightly out of the insertion opening (15). When the hanger (13) is released, it returns to the normal position (N) again, due to its own weight and the weight of the articles hanging on it. This hanging device allows the hangers (13) to be arranged closely adjacently. However, easy access to the articles is possible because the hangers (13) can easily be swivelled. Since they always return to the normal position again, the hanging device with the articles accommodated on it always leaves a tidy impression. <IMAGE>

IPC 1-7

A47F 5/08; A47F 7/10

IPC 8 full level

A47F 5/08 (2006.01); **A47F 7/10** (2006.01)

CPC (source: EP)

A47F 5/0807 (2013.01); **A47F 5/0838** (2013.01); **A47F 7/10** (2013.01)

Cited by

EP0634126A1; FR2712161A1

Designated contracting state (EPC)

AT DE FR IT

DOCDB simple family (publication)

CH 667002 A5 19880915; AT E77219 T1 19920715; DE 58901646 D1 19920723; EP 0328490 A2 19890816; EP 0328490 A3 19900110; EP 0328490 B1 19920617

DOCDB simple family (application)

CH 49688 A 19880211; AT 89810111 T 19890210; DE 58901646 T 19890210; EP 89810111 A 19890210