

Title (en)

SUPPORTING DEVICE FOR A SOOT BLOWER

Publication

**EP 0330817 B1 19910515 (DE)**

Application

**EP 89100704 A 19890117**

Priority

DE 3805679 A 19880224

Abstract (en)

[origin: EP0330817A1] A soot blower is attached in a hinged fashion to the wall (1) of a heat exchanger, and suspended on a frame via a lever strutting. The lever strutting consists of two double-armed levers (12, 13), which are mounted in each case in a lever bearing (14, 15) and are connected to one another via a coupling hinge (17). The free end of one lever (12) is connected in a hinged fashion to the wall (1) of the heat exchanger, and the free end of the other lever (13) is connected in a hinged fashion to the soot blower. The lever bearings (14, 15) are suspended on the frame and can, just like the coupling hinge (17) be displaced in the longitudinal direction of the lever (12, 13). <IMAGE>

IPC 1-7

**F28G 15/02**

IPC 8 full level

**F28G 15/02** (2006.01)

CPC (source: EP)

**F28G 15/02** (2013.01)

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

**EP 0330817 A1 19890906; EP 0330817 B1 19910515;** AT E63637 T1 19910615; DE 3805679 A1 19890907; DE 58900114 D1 19910620; ES 2022725 B3 19911201; GR 3001956 T3 19921123

DOCDB simple family (application)

**EP 89100704 A 19890117;** AT 89100704 T 19890117; DE 3805679 A 19880224; DE 58900114 T 19890117; ES 89100704 T 19890117; GR 910400581 T 19910516