

Title (en)

PUSHER CENTRIFUGE

Publication

EP 0331924 B1 19921223 (DE)

Application

EP 89102291 A 19890210

Priority

CH 83488 A 19880307

Abstract (en)

[origin: JPH01274856A] PURPOSE: To greatly enhance a dehydration rate by diagonally directing the blade members of the outer edge of a pushing ring and constituting these blade members in such a manner that the additive motion component in the circumferential direction of a sieve drum is applied to feedstock for sepn. by accompanying vibration motion. CONSTITUTION: The outer edge of the inner sieve drum 1 is provided with the many blade members 12. These blade members 12 are so constituted as to have the pushing surface inclined with the axial line of the sieve drum and eventually the axial line of rotation thereof. The feedstock for sepn. is then additionally subjected to the motion component in the circumferential direction by such blade members 12 accompanying the each other's vibration of both sieve drums 1, 2. Then, the capillary layer to hinder the permeation of the filtrate formed on the inside surface of the sieve drum 2 as a result of receiving the incessant transportation impulse is destroyed and removed by a shearing effect. Consequently, a large filtrate amt. and eventually a great improvement in the dehydration efficiency are obtd. even in the case of the same centrifugal force.

IPC 1-7

B04B 3/02

IPC 8 full level

B04B 3/02 (2006.01)

CPC (source: EP US)

B04B 3/02 (2013.01 - EP US)

Designated contracting state (EPC)

BE DE ES FR GB IT NL SE

DOCDB simple family (publication)

DE 3810565 C1 19890713; BR 8900818 A 19891017; CH 675374 A5 19900928; CN 1017407 B 19920715; CN 1036714 A 19891101;
DE 58903062 D1 19930204; EP 0331924 A2 19890913; EP 0331924 A3 19900321; EP 0331924 B1 19921223; ES 2037888 T3 19930701;
JP H01274856 A 19891102; JP H0624648 B2 19940406; US 4889627 A 19891226

DOCDB simple family (application)

DE 3810565 A 19880329; BR 8900818 A 19890223; CH 83488 A 19880307; CN 89101210 A 19890307; DE 58903062 T 19890210;
EP 89102291 A 19890210; ES 89102291 T 19890210; JP 5307589 A 19890307; US 31419589 A 19890223