

Title (en)

CONTROL METHOD FOR A YARN STORAGE AND DELIVERY DEVICE AS WELL AS STORAGE AND DELIVERY DEVICE

Publication

**EP 0332164 B1 19920617 (DE)**

Application

**EP 89104103 A 19890308**

Priority

SE 8800839 A 19880309

Abstract (en)

[origin: WO8908600A1] A process serves to control a device for storing and forwarding yarn, in particular for a loom, on the storage surface of which the yarn can be wound in coils and drawn off by a consumer. A control unit for a take-up drive adjusts the take-up speed in function of the use at least by means of the actual member of coils on the storage surface, in order to match the actual value to a predetermined target value. The target value is varied at least during changes in the take-up speed, in order to obtain an optimally compact supply of yarn on the storage surface. In a device for storing and forwarding yarn by this process, the control unit (8) is associated with a generator of reference variables (18) for the target values (nV), which vary in a predetermined manner, whereby the target values (nV) vary continuously.

IPC 1-7

**B65H 51/22**; **D03D 47/36**

IPC 8 full level

**B65H 51/22** (2006.01); **D03D 47/36** (2006.01)

CPC (source: EP KR US)

**B65H 51/22** (2013.01 - KR); **D03D 47/367** (2013.01 - EP US)

Cited by

US5377922A; WO9118818A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

**EP 0332164 A1 19890913**; **EP 0332164 B1 19920617**; AT E77345 T1 19920715; BR 8907306 A 19910319; JP 2766939 B2 19980618; JP H03503298 A 19910725; KR 0170753 B1 19990330; KR 900700374 A 19900813; SE 8800839 D0 19880309; US 5119998 A 19920609; WO 8908600 A1 19890921

DOCDB simple family (application)

**EP 89104103 A 19890308**; AT 89104103 T 19890308; BR 8907306 A 19890308; EP 8900241 W 19890308; JP 50319089 A 19890308; KR 890702071 A 19891108; SE 8800839 A 19880309; US 61347590 A 19901026