Title (en)

## PRINTER WITH A PLURALITY OF EXIT PATHS FOR RECORD CARRIERS

Publication

EP 0332873 B1 19920506 (DE)

Application

EP 89102676 A 19890216

Priority

DE 8803496 U 19880315

Abstract (en)

[origin: EP0332873A1] A printer with a printing station, a first feeding device for record carriers in the form of a continuous web (16), at least one second feeding device for record carriers in the form of single sheets (30) and delivery channels for the continuous web or the single sheets. Behind the printing station in the transport direction a deflector device (20) is arranged which guides the respective record carriers into the delivery channel appropriate to them. It comprises at least two folding deflector elements (36, 38) which directly at the exit of the printing station (12, 14) substantially extend over the width of the transport web for the record carriers (16, 30) and which are hinge-mounted on axes (40, 44) parallel to one another and at right angles to the transport web in such a manner that a first delivery channel can be opened between them and further delivery channels can be opened between one respective deflector element (36, 38) and a stationary guidance surface (52 or 50). More than two delivery channels can be actuated by different constellations of the deflector elements (36, 38). <IMAGE>

IPC 1-7

B41J 11/48; B41J 13/00

IPC 8 full level

B41J 11/48 (2006.01); B41J 13/00 (2006.01); B41J 13/10 (2006.01)

CPC (source: EP)

B41J 13/103 (2013.01); B41J 13/106 (2013.01)

Cited by

DE102009038175A1; FR2813038A1; EP0473167A1; US5966158A; EP1431940A3; US8764011B2; US6981636B2

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

DE 8803496 U1 19880511; DE 58901304 D1 19920611; EP 0332873 A1 19890920; EP 0332873 B1 19920506

DOCDB simple family (application)

**DE 8803496 U 19880315**; DE 58901304 T 19890216; EP 89102676 A 19890216