

Title (en)
Heat-resistant resin composition.

Title (de)
Hitzebeständige Harzzusammensetzung.

Title (fr)
Composition de résins résistant au chaleur.

Publication
EP 0333002 A2 19890920 (EN)

Application
EP 89104047 A 19890308

Priority
JP 5946688 A 19880315

Abstract (en)
A heat-resistant resin composition comprising (A) 10 to 80% by weight of aromatic polycarbonate resin, (B) 10 to 80% by weight of polyarylate, (C) 10 to 20% by weight of polyamide, and (D) 1 to 15 parts by weight of rubber-like elastomer to 100 parts by weight of the above (A), (B) and (C) in total is disclosed. The resin composition can be widely used as material for injection molding, extrusion molding, compression molding, calendar molding, rotary molding, the molding for cars including bumpers, and moldings for house electric appliances.

IPC 1-7
C08L 67/02; C08L 69/00; C08L 77/00

IPC 8 full level
C08L 67/00 (2006.01); C08L 67/02 (2006.01); C08L 67/03 (2006.01); C08L 69/00 (2006.01)

CPC (source: EP KR)
C08L 67/02 (2013.01 - KR); C08L 67/03 (2013.01 - EP); C08L 69/00 (2013.01 - EP KR)

Cited by
EP0451769A3; EP0437786A1; EP0374887A3

Designated contracting state (EPC)
BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)
EP 0333002 A2 19890920; EP 0333002 A3 19900314; EP 0333002 B1 19940427; BR 8901190 A 19891031; DE 68914870 D1 19940601; DE 68914870 T2 19941020; JP H01234460 A 19890919; JP H0613640 B2 19940223; KR 890014679 A 19891025; KR 950011910 B1 19951012

DOCDB simple family (application)
EP 89104047 A 19890308; BR 8901190 A 19890315; DE 68914870 T 19890308; JP 5946688 A 19880315; KR 890003222 A 19890315