

Title (en)
ELECTROMAGNETIC RELAY

Publication
EP 0333717 B1 19911030 (DE)

Application
EP 87906810 A 19871024

Priority
DE 3640997 A 19861201

Abstract (en)
[origin: WO8804466A1] Electromagnetic relay comprising a switching contact (20) which is pivoted from the rest position to the operating position by a snap-element (18) when the relay is actuated. In order to achieve a specific contact pressure on the switching contact (20) when the snap-element (18) is applied, the operating contact (24) is provided with an excursion region (35) on the contact support (25). Simple, rapid and precise adjustment of the working contact (24) is made possible by the fact that the contact support (25) consists, in the direction of movement of the snap anchor (18), of three bars (29, 30, 31) which extend at a distance from one another, ending in a joint yoke (32), and of which the centre bar (30) carries the angled operating contact (24) and is connected on both sides by symmetrically arranged connection pieces (33, 34) with the two external bars (29, 31). The excursion region (35) for axial shifting of the operating contact (24) is located on the central arm (30) between the yoke (32) and the connection pieces (33, 34).

IPC 1-7
H01H 1/34

IPC 8 full level
H01H 1/34 (2006.01); **H01H 50/54** (2006.01); **H01H 50/56** (2006.01); **H01H 50/60** (2006.01)

CPC (source: EP KR US)
H01H 1/34 (2013.01 - KR); **H01H 50/546** (2013.01 - EP US); **H01H 1/34** (2013.01 - EP US); **H01H 50/60** (2013.01 - EP US)

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
DE 3640997 C1 19871210; DE 3774278 D1 19911205; EP 0333717 A1 19890927; EP 0333717 B1 19911030; JP H02500786 A 19900315;
KR 890700258 A 19890310; US 4926150 A 19900515; WO 8804466 A1 19880616

DOCDB simple family (application)
DE 3640997 A 19861201; DE 3774278 T 19871024; DE 8700481 W 19871024; EP 87906810 A 19871024; JP 50661787 A 19871024;
KR 880700904 A 19880730; US 34325889 A 19890414